





### Location Map

Project: Woodhaven at Minnetonka  
Address: 2424 & 2440 Plymouth Rd




# WOODHAVEN OF MINNETONKA


R.T. DOC. NO. \_\_\_\_\_  
C.R. DOC. NO. \_\_\_\_\_



SECTION 10, TWP. 117, RGE. 22  
HENNEPIN COUNTY, MINNESOTA  
**LOCATION MAP**  
NOT TO SCALE




**DRAINAGE AND UTILITY EASEMENTS ARE SHOWN THUS:**




Being 5 feet in width, and adjoining lot lines unless otherwise indicated, and 10 feet in width and adjoining right of way and rear lot lines unless otherwise indicated on the plat.

THE ORIENTATION OF THIS BEARING SYSTEM IS BASED ON THE SOUTH LINE OF THE NORTHEAST QUARTER OF SEC. 10, TWP. 117, RGE. 22, WHICH IS ASSUMED TO HAVE A BEARING OF NORTH 89°21'40\"/>


- DENOTES FOUND CAST IRON MONUMENT
- DENOTES 1/2 INCH BY 14 INCH IRON PIPE MONUMENT SET AND MARKED BY LICENSE NUMBER 42299.
- DENOTES FOUND 1/2 INCH IRON MONUMENT MARKED BY LICENSE NUMBER 42299 UNLESS OTHERWISE NOTED.



# WOODHAVEN GRADING, UTILITY & STREET CONSTRUCTION PLAN MINNETONKA, MINNESOTA




LOCATION MAP



## SHEET INDEX

COVER .....	1.10
LEGEND .....	1.20
REMOVAL PLAN .....	2.10
SITE PLAN .....	3.10
GRADING PLAN .....	4.10
EROSION CONTROL PLAN .....	4.20
SEEDING PLAN .....	4.30
GRADING DETAILS .....	4.40-4.42
WETLAND PLAN .....	5.10
SANITARY SEWER & WATERMAIN PLAN .....	6.10
STORM SEWER PLAN .....	7.10
STREET CONSTRUCTION .....	8.10
DETAILS .....	9.10-9.12
STORM WATER POLLUTION PREVENTION PLAN .....	S1-S2
MPCA MAP .....	S3
EXISTING HYDROLOGY MAP .....	S4
PROPOSED HYDROLOGY MAP .....	S5
LANDSCAPE PLAN .....	L1
TREE PRESERVATION PLAN .....	T1-T3



2422 Enterprise Drive  
Mendota Heights, MN 55120  
(651) 681-1914  
Fax: 681-9488  
www.pioneereng.com

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.

Name: John M. Molinaro  
Reg. No.: 45831  
Date: 3-15-2024

Revisions

Date: 3-15-24  
Designed: JMM  
Drawn: MSN/PDS

COVER

NORTON HOMES  
18215 45TH AVENUE NORTH  
PLYMOUTH, MINNESOTA 55446



WOODHAVEN  
MINNETONKA, MINNESOTA

01-ENG-123127-SHEET-COVR



LEGEND			
<b>EXISTING</b>	<b>PROPOSED</b>	<b>FUTURE</b>	<b>DESCRIPTION</b>
			SANITARY MANHOLE
			SANITARY SEWER (SANITARY & WATERMAIN PLANS)
			SANITARY SEWER (STORM SEWER PLANS)
			FORCE MAIN
			HYDRANT
			GATE VALVE
			REDUCER
			CURB STOP
			WATERMAIN (SANITARY & WATERMAIN PLANS)
			WATERMAIN (STORM SEWER PLANS)
			CATCH BASIN
			BEEHIVE
			STORM MANHOLE
			FLARED END SECTION
			CONTROL STRUCTURE
			STORM SEWER (SANITARY & WATERMAIN PLANS)
			STORM SEWER (STORM SEWER PLANS)
			CULVERT
			PERFORATED DRAINTILE
			SOLID DRAINTILE SERVICE
			CASING
			UNDERGROUND ELECTRIC LINE
			UNDERGROUND FIBER OPTIC LINE
			UNDERGROUND GAS PIPELINE
			UNDERGROUND PETROLEUM PIPELINE
			UNDERGROUND TELEPHONE LINES
			UNDERGROUND TELEVISION LINE
			OVERHEAD UTILITY LINES
<b>EXISTING</b>	<b>PROPOSED</b>	<b>FUTURE</b>	<b>DESCRIPTION</b>
			SURMOUNTABLE CURB & GUTTER
			B-STYLE CURB & GUTTER
			RIBBON CURB & GUTTER
			EDGE OF BITUMINOUS
			YELLOW PAVEMENT STRIPING (SINGLE/DOUBLE)
			WHITE PAVEMENT STRIPING (SINGLE/DOUBLE)
			PHASE LINE
			CENTERLINE
			2' CONTOUR LINE
			10' CONTOUR LINE
			BASIN OUTLET LINE
			BASIN HIGH WATER LINE
			PROPOSED SPOT ELEVATION
			EMERGENCY OVERFLOW
			DRAINAGE FLOW ARROW
			DELINEATED / PROPOSED WETLAND LINE
			WETLAND BUFFER
			TREE LINE
			FEMA FLOODPLAIN BOUNDARY
			RETAINING WALL
			FENCE (BARBED WIRE)
			FENCE (CHAIN LINK)
			FENCE (WOOD)
			CONSERVATION AREA SIGN
			WETLAND BUFFER SIGN
			TYPE III BARRICADE
			LIGHT POLE
			STREET SIGNS
			PEDESTRIAN RAMP
<b>EXISTING</b>	<b>PROPOSED</b>	<b>FUTURE</b>	<b>DESCRIPTION</b>
			BOUNDARY
			RIGHT OF WAY
			LOT LINE
			EASEMENT
			SET BACK LINE
			SECTION LINE
			RESTRICTED ACCESS
HATCH PATTERNS			
	GRAVEL SURFACE		WETLAND
	BITUMINOUS SURFACE		WETLAND UPLAND BUFFER
	CONCRETE SURFACE		WETLAND MITIGATION
	RIP RAP		PERMANENT TURF RESTORATION
	SELECT BACKFILL MATERIAL		PERMANENT WET BASIN SEEDING
	EROSION CONTROL BLANKET MNDOT CATEGORY PER PLAN		UPLAND/NATURAL AREA SEEDING

TOPOGRAPHIC SYMBOLS	
	CATCH BASIN
	CATCH BASIN BEEHIVE
	FLARED END SECTION
	GATE VALVE
	HYDRANT
	WATER SERVICE
	WATER WELL
	MONITORING WELL
	CLEANOUT
	HAND HOLE
	MANHOLE OTHER THAN SANITARY OR STORM
	SANITARY OR STORM MANHOLE
	LAWN SPRINKLER VALVE
	LAWN SPRINKLER HEAD
	UTILITY POLE
	TRANSFORMER BOX
	FIBER OPTIC BOX
	ELECTRIC BOX
	NATURAL GAS METER
	LIGHT POLE
	SEMAPHORE
	TELEPHONE BOX
	CABLE BOX
	CAST IRON MONUMENT
	FOUND IRON PIPE
	JUDICIAL LAND MARK
	PK NAIL
	CONTROL POINT
	SPIKE
	FLAG POLE
	TEST HOLE
	MAILBOX
	SIGN
	BOLLARD
	CONSERVATION POST
	DECIDUOUS TREE
	CONIFEROUS TREE
	SHRUB / BUSH
EROSION & SEDIMENT CONTROL	
	STANDARD EROSION CONTROL
	HEAVY-DUTY EROSION CONTROL
	SECONDARY EROSION CONTROL FENCE
	EROSION CONTROL AT BACK OF CURB
	TREE FENCE
	TEMPORARY DIVERSION DITCH
	CATCH BASIN INLET PROTECTION
	STRAW BIO ROLLS
	ROCK BERM
	SUMPED RIP RAP PERMANENT ENERGY DISSIPATER
	DISCHARGE LOCATION
	GRAVEL CONSTRUCTION ENTRANCE
	TEMPORARY OUTLET FLOATING SKIMMER
	BASIN ACCESS 8% SLOPE MAX.
	STABILIZED EMERGENCY OVERFLOW
	STEEP SLOPE 3:1 (H:V) (33.3%) OR STEEPER GRADE

ABBREVIATIONS	
A	ALGEBRAIC DIFFERENCE
B-B	BACK TO BACK
BV	BUTTERFLY VALVE
BOC	BACK OF CURB
BFE	BASE FLOOD ELEVATION
BMP	BEST MANAGEMENT PRACTICE
C	CENTER LINE
CB	CATCHBASIN
CBMH	CATCHBASIN MANHOLE
CMP	CORRUGATED METAL PIPE
CO	CLEAN OUT
CS	CURB STOP
DIP	DUCTILE IRON PIPE
DT	DRAINTILE
EL/ELEV	ELEVATION
EX	EXISTING
FES	FLARED END SECTION
F-F	FACE TO FACE
FM	FORCEMAIN
GB	GRADE BREAK
GND	GROUND
GV	GATE VALVE
HP	HIGH POINT
HYD	HYDRANT
HWL	HIGH WATER LEVEL
INV	INVERT
K	CURVE COEFFICIENT
L	LENGTH
LF	LOWEST FLOOR
LO	LOOKOUT
LO	LOWEST OPENING
LP	LIQUID PETROLEUM
LP	LOW POINT
MH	MANHOLE
PC	POINT OF CURVATURE
PCC	POINT OF COMPOUND CURVATURE
PI	POINT OF INTERSECTION
R	PROPERTY LINE
PRC	POINT OF REVERSE CURVATURE
PVT	POINT OF TANGENCY
PVC	POINT OF VERTICAL CURVATURE
PVC	POLYVINYL CHLORIDE PIPE
PVI	POINT OF VERTICAL INTERSECTION
R	RADIUS
R	RAMBLER
RCP	REINFORCED CONCRETE PIPE
ROW	RIGHT OF WAY
SSWR	SANITARY SEWER
STA	STATION
STRM	STORM SEWER
SWPPP	STORM WATER POLLUTION PROTECTION PLAN
TNH	TOP NUT HYDRANT
TYP	TYPICAL
WM	WATER MAIN
WO	WALKOUT

LOT INFORMATION	
(TYPICAL SECTION NOT TO SCALE)	
	<p>29.0</p> <p>28.0</p> <p>35.5</p> <p>34.5</p> <p>29.0</p> <p>28.0</p> <p>931.5</p> <p>LO=929.0</p> <p>1' STEP</p> <p>LF=929.0</p> <p>LG=37.0</p> <p>35.5</p> <p>34.5</p>
<p>DRAINAGE &amp; UTILITY EASEMENT</p> <p>FINISHED GROUND ELEVATION</p> <p>LOWEST OPENING ELEVATION</p> <p>STEP HEIGHT (IF REQUIRED)</p> <p>LOWEST FLOOR ELEVATION</p> <p>GARAGE ELEVATION</p> <p>RECOMMENDED GARAGE SIDE</p> <p>FINISHED ELEVATION</p> <p>LOT CORNER</p>	<p>BLOCK NO. 7</p> <p>LOT NO. 7</p> <p>HOUSE TYPES</p> <p>R — RAMBLER OR SPLIT ENTRY</p> <p>LO — RAMBLER LOOKOUT OR SPLIT ENTRY WALKOUT</p> <p>WO — RAMBLER WALKOUT</p> <p>SE — SPLIT ENTRY</p> <p>SEWO — SPLIT ENTRY WALK OUT</p> <p>SLO — SIDE LOOKOUT</p> <p>SWO — SIDE WALKOUT</p>







2040 COMP PLAN: LOW DENSITY RESIDENTIAL (1-4 UNITS/ACRE)  
 CURRENT ZONING: R-1  
 PROPOSED ZONING: R-1

R-1 MINIMUM BULK STANDARDS:  
 AREA: 22,000 SF  
 WIDTH: 110'  
 DEPTH: 125'  
 FRONT SETBACK: 35'  
 SIDE SETBACK: 10' MINIMUM, 30' COMBINED  
 REAR YARD: LESSER OF 40' OR 20% OF LOT DEPTH  
 DRIVEWAY EASEMENT: 7' FROM DRIVEWAY


STORMWATER REQUIREMENTS  
 LOW OPENING 2'+HWL  
 LOW FLOOR 2'+HWL





STORMWATER REQUIREMENTS  
 LOW OPENING 2'+HWL  
 LOW FLOOR 2'+HWL

FILTRATION AREA



**PIONEER engineering**  
 CIVIL ENGINEERS LAND PLANNERS LAND SURVEYORS LANDSCAPE ARCHITECTS

2422 Enterprise Drive  
 Mendota Heights, MN 55120  
 (651) 681-1914  
 Fax: 681-9488  
 www.pioneereng.com

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota.  
 Name: John M. Molinaro  
 Reg. No.: 45831  
 Date: 3-15-2024


Revisions  
 Date: 3-15-24  
 Designed: JMM  
 Drawn: MSN/PDS

**GRADING PLAN**












**NORTON HOMES**  
 18215 45TH AVENUE NORTH  
 PLYMOUTH, MINNESOTA 55446


**WOODHAVEN**  
 MINNETONKA, MINNESOTA

4.10 OF 22



**LEGEND**

-  ROCK CONSTRUCTION ENTRANCE. INSTALL BEFORE START OF GRADING.
-  PERIMETER EROSION CONTROL FENCE. INSTALL BEFORE START OF GRADING.
-  SECONDARY EROSION CONTROL FENCE. TO BE INSTALLED 48 HOURS AFTER COMPLETION OF GRADING.
-  2' SOD OR EROSION CONTROL FENCE AT BACK OF CURB. TO BE INSTALLED AFTER COMPLETION OF SIDEWALK CONSTRUCTION.
-  SUMPED RIP RAP PERMANENT ENERGY DISSIPATER. INSTALL WITHIN 24 HOURS AFTER CONNECTION TO A SURFACE WATER.
-  STABILIZED EMERGENCY OVERFLOW
-  MNDOT CAT 3 EROSION CONTROL BLANKET. INSTALL WITHIN 7 DAYS OF GRADING COMPLETION
-  CATCH BASIN INLET PROTECTION TO BE INSTALLED AFTER 1ST LIFT OF BITUMINOUS.
-  CATCH BASIN INLET PROTECTION TO BE INSTALLED WITH CATCH BASIN GRATE.
-  WETLAND CONSERVATION SIGN
-  FILTRATION AREA









- TEMPORARY SEED SHALL BE DONE IN ACCORDANCE TO MNDOT 2575 & 3876; CONSISTING OF:
- MAY 1 – AUGUST 1: MINNESOTA STATE SEED MIXTURE 22-111 (OATS COVER CROP) @ 100.0 LBS. PER ACRE OR APPROVED EQUAL.
  - AUGUST 1 – OCTOBER 1: MINNESOTA STATE SEED MIXTURE 22-111 (WINTER WHEAT COVER CROP) @ 100.0 LBS. PER ACRE OR APPROVED EQUAL.
  - MULCH SHALL BE MNDOT 3882, TYPE 1 @ 2 TONS PER ACRE OR APPROVED EQUAL AND DISK ANCHORED IN PLACE OR APPROVED EQUAL, INSTALLED TO MINIMUM 90% COVERAGE OF THE SURFACE AREA DISTURBED.
  - MNDOT 3881, TYPE 1 COMMERCIAL FERTILIZER, 10-10-20 @ 200 LBS. PER ACRE
- PERMANENT TURF RESTORATION SHALL BE DONE IN ACCORDANCE WITH MNDOT 2575 & 3876 CONSISTING OF:
- MINNESOTA STATE SEED MIXTURE 25-141 (MESIC GENERAL ROADSIDE) AT 59 POUNDS PER ACRE.
  - MULCH SHALL BE MNDOT 3882, TYPE 1 @ 2 TONS PER ACRE OR APPROVED EQUAL AND DISK ANCHORED IN PLACE OR APPROVED EQUAL, INSTALLED TO MINIMUM 90% COVERAGE OF THE SURFACE AREA DISTURBED.
  - MNDOT 3881, TYPE 3 SLOW-RELEASE FERTILIZER, 22-5-10, MINIMUM 70% WATER-INSOLUBLE NITROGEN @ 350 LBS PER ACRE.
- PERMANENT BASIN SEEDING SHALL BE DONE IN ACCORDANCE WITH MNDOT 2575 & 3876 CONSISTING OF:
- WET BASIN BENCH/(IN)FILTRATION BASIN: MINNESOTA STATE SEED MIXTURE 33-261 (STORMWATER SOUTH AND WEST) AT 35 POUNDS PER ACRE.
  - ABOVE BASIN BENCH TO HIGH WATER LEVEL: MINNESOTA STATE SEED MIXTURE 35-241 (MESIC PRAIRIE GENERAL) AT 36.5 POUNDS PER ACRE.
  - MULCH SHALL BE MNDOT 3882, TYPE 3 @ 2 TONS PER ACRE OR APPROVED EQUAL AND DISK ANCHORED IN PLACE OR APPROVED EQUAL.
  - MNDOT 3881, TYPE 4 NATURAL-BASED FERTILIZER, 18-1-8 @ 120 LBS PER ACRE OR 17-10-7 @ 150 LBS PER ACRE

- PERMANENT TURF RESTORATION SHALL BE DONE IN ACCORDANCE WITH MNDOT 2575 & 3876 CONSISTING OF:
- MINNESOTA STATE SEED MIXTURE 36-211 (WOODLAND EDGE SOUTH & WEST) AT 34.5 POUNDS PER ACRE.
  - MULCH SHALL BE MNDOT 3882, TYPE 1 @ 2 TONS PER ACRE OR APPROVED EQUAL AND DISK ANCHORED IN PLACE OR APPROVED EQUAL, INSTALLED TO MINIMUM 90% COVERAGE OF THE SURFACE AREA DISTURBED.
  - MNDOT 3881, TYPE 3 SLOW-RELEASE FERTILIZER, 10-20-20, MINIMUM 70% WATER-INSOLUBLE NITROGEN @ 300 LBS PER ACRE.





PLANTING MEDIUM SHALL MEET MINNESOTA STORMWATER MANUAL BIO-RETENTION MEDIA COMPOSITION MIX C (SEE MANUAL FOR ADDITIONAL MIX REQUIREMENTS)

- MIX C:
- 85 TO 88 PERCENT BY VOLUME SAND
  - 8 TO 12 PERCENT FINES BY VOLUME (SILT AND CLAY)
  - 3 TO 5 PERCENT ORGANIC MATTER BY WEIGHT
- MNDOT GRADE 2 COMPOST IS RECOMMENDED

SCARIFY BOTTOM 12"–18" BEFORE PLACING AMENDED SOILS

UNDISTURBED, UNCOMPACTED INSITU SOIL

6" PERF. PVC

**FILTRATION BASIN CONSTRUCTION NOTES**


**CONSTRUCTION SEQUENCING**

1. INSTALL SILT FENCE AND/OR OTHER APPROPRIATE EROSION CONTROL DEVICES TO PREVENT SEDIMENT FROM LEAVING OR ENTERING THE PRACTICE DURING CONSTRUCTION.
2. ALL DOWN-GRADIENT PERIMETER SEDIMENT CONTROL BMPs MUST BE IN PLACE BEFORE ANY UP GRADIENT LAND DISTURBING ACTIVITY BEGINS.
3. PERFORM CONTINUOUS INSPECTIONS OF EROSION CONTROL PRACTICES.
4. INSTALL UTILITIES (WATER, SANITARY SEWER, ELECTRIC, PHONE, FIBER OPTIC, ETC) PRIOR TO SETTING FINAL GRADE OF RETENTION DEVICE.
5. ROUGH GRADE THE SITE. DO NOT USE RETENTION AREA AS TEMPORARY SEDIMENT BASINS.
6. PERFORM ALL OTHER SITE IMPROVEMENTS.
7. SEED AND MULCH ALL AREAS AFTER DISTURBANCE.
8. CONSTRUCT RETENTION DEVICE UPON STABILIZATION OF CONTRIBUTING DRAINAGE AREA.
9. IMPLEMENT TEMPORARY AND PERMANENT EROSION CONTROL PRACTICES.
10. PLANT AND MULCH RETENTION DEVICE.
11. REMOVE TEMPORARY EROSION CONTROL DEVICES AFTER THE CONTRIBUTING DRAINAGE AREA IS ADEQUATELY VEGETATED.


**GENERAL NOTES**

1. IN THE EVENT THAT SEDIMENT IS INTRODUCED INTO THE BMP DURING OR IMMEDIATELY FOLLOWING EXCAVATION, THIS MATERIAL SHALL BE REMOVED FROM THE PRACTICE PRIOR TO CONTINUING CONSTRUCTION.
2. GRADING OF RETENTION DEVICES SHALL BE ACCOMPLISHED USING LOW-COMPACTION EARTH-MOVING EQUIPMENT TO PREVENT COMPACTION OF UNDERLYING SOILS.
3. ALL SUB MATERIALS BELOW THE SPECIFIED BIORETENTION DEPTH (ELEVATION) SHALL BE UNDISTURBED, UNLESS OTHERWISE NOTED.


**FILTRATION BASIN CROSS SECTION**  
(TYPICAL SECTION NOT TO SCALE)




**STABILIZED EMERGENCY OVERFLOW DETAIL**  
SECTION B-B




**STABILIZED EMERGENCY OVERFLOW DETAIL**  
SECTION A-A




**LOT INFORMATION**  
(TYPICAL SECTION NOT TO SCALE)




**SUBGRADE CORRECTION**  
(TYPICAL SECTION NOT TO SCALE)




**RAMBLER**  
(TYPICAL SECTION NOT TO SCALE)




**LOOKOUT**  
(TYPICAL SECTION NOT TO SCALE)




**WALKOUT**  
(TYPICAL SECTION NOT TO SCALE)




**10' WALKOUT**  
(TYPICAL SECTION NOT TO SCALE)




MINNESOTA DEPARTMENT OF TRANSPORTATION  
 STANDARD PLAN 5-297.405 1 OF 8  
 APPROVED: 2-28-2017  
 STATE PROJ. NO. (T.H. ) SHEET NO. OF SHEETS  
**TEMPORARY SEDIMENT CONTROL SILT CURTAIN OR SILT FENCE TYPE TB**




MINNESOTA DEPARTMENT OF TRANSPORTATION  
 STANDARD PLAN 5-297.405 2 OF 8  
 APPROVED: 1-8-2020  
 STATE PROJ. NO. (T.H. ) SHEET NO. OF SHEETS  
**TEMPORARY SEDIMENT CONTROL FILTER BERMS, SEDIMENT CONTROL LOGS, AND BALE BARRIERS**



MINNESOTA DEPARTMENT OF TRANSPORTATION  
 STANDARD PLAN 5-297.405 3 OF 8  
 APPROVED: 1-8-2020  
 STATE PROJ. NO. (T.H. ) SHEET NO. OF SHEETS  
**TEMPORARY SEDIMENT CONTROL DITCH CHECK**




MINNESOTA DEPARTMENT OF TRANSPORTATION  
 STANDARD PLAN 5-297.405 4 OF 8  
 APPROVED: 2-28-2017  
 STATE PROJ. NO. (T.H. ) SHEET NO. OF SHEETS  
**TEMPORARY SEDIMENT CONTROL STORM DRAIN INLET PROTECTION**




- NOTES:**  
 SEE SPECS. 2573 & 3882.  
 ① MINIMUM LENGTH SHALL BE THE GREATER OF 50 FEET OR A LENGTH SUFFICIENT TO ALLOW A MINIMUM OF 3 TIRE ROTATIONS ON THE PROVIDED PAD. MINIMUM LENGTH SHALL BE CALCULATED USING THE LARGEST TIRE WHICH WILL BE USED IN TYPICAL OPERATIONS.  
 ② PROVIDE RADIUS OR WIDEN PAD SUFFICIENTLY TO PREVENT VEHICLE TIRES FROM TRACKING OFF OF PAD WHEN LEAVING SITE.  
 ③ IF RUNOFF FROM DISTURBED AREAS FLOWS TOWARD CONSTRUCTION EXITS, PREVENT RUNOFF FROM DRAINING DIRECTLY TO PUBLIC ROAD OVER CONSTRUCTION EXIT BY CROWNING THE EXIT OR SLOPING TO ONE SIDE. IF SURFACE GRADING IS INSUFFICIENT, PROVIDE OTHER MEANS OF INTERCEPTING RUNOFF.  
 ④ IF RUNOFF FROM CONSTRUCTION EXITS WILL DRAIN OFF OF PROJECT SITE, PROVIDE SEDIMENT TRAP WITH STABILIZED OVERFLOW.  
 ⑤ IF A TIRE WASH OFF IS REQUIRED THE CONSTRUCTION EXITS SHALL BE GRADED TO DRAIN THE WASH WATER TO A SEDIMENT TRAP.  
 ⑥ MINIMUM LENGTH OF RUMBLE PAD SHALL BE 20 FEET, OR AS REQUIRED TO REMOVE SEDIMENT FROM TIRES. IF SIGNIFICANT SEDIMENT IS TRACKED FROM THE SITE, THE RUMBLE PAD SHALL BE LENGTHENED OR THE DESIGN MODIFIED TO PROVIDE ADDITIONAL VIBRATION. WASH-OFF LENGTH SHALL BE AS REQUIRED TO EFFECTIVELY REMOVE CONSTRUCTION SEDIMENT FROM VEHICLE TIRES.  
 ⑦ MAINTENANCE OF CONSTRUCTION EXITS SHALL OCCUR WHEN THE EFFECTIVENESS OF SEDIMENT REMOVAL HAS BEEN REDUCED. MAINTENANCE SHALL CONSIST OF REMOVING SEDIMENT AND CLEANING THE MATERIALS OR PLACING ADDITIONAL MATERIAL (SLASH MULCH OR CRUSHED ROCK OVER SEDIMENT FILLED MATERIAL) TO RESTORE EFFECTIVENESS.

STANDARD PLAN 5-297.405 DEPARTMENT OF TRANSPORTATION STATE DESIGN ENGINEER	5 OF 8 APPROVED: 2-28-2017 REVISION:	<b>TEMPORARY SEDIMENT CONTROL</b> STABILIZED CONSTRUCTION EXIT STATE PROJ. NO. (T.H.) SHEET NO. OF SHEETS
--	--	---




- NOTES:**  
 SEE SPECS. 2573, 3149 & 3886.  
 ① COARSE FILTER AGGREGATE (SPEC. 3149) SHALL BE INCIDENTAL.  
 ② TO PROTECT AREAS FROM SHEET FLOW, MAXIMUM CONTRIBUTING AREA: 1 ACRE.  
 ③ TO PROTECT AREAS FROM SHEET FLOW, MAXIMUM CONTRIBUTING AREA: 0.25 ACRE.  
 ④ WATER COURSE FLOW VELOCITY: STANDING, CONTRIBUTING SLOPE AREA: 1/2 ACRE.  
 ⑤ WATER COURSE FLOW VELOCITY: 1 TO 7 FT./SEC., CONTRIBUTING SLOPE AREA: 1 ACRE.  
 ⑥ WATER COURSE FLOW VELOCITY: 8 TO 15 FT./SEC., CONTRIBUTING SLOPE AREA: 3 ACRES.

STANDARD PLAN 5-297.405 DEPARTMENT OF TRANSPORTATION STATE DESIGN ENGINEER	6 OF 8 APPROVED: 2-28-2017 REVISION:	<b>TEMPORARY SEDIMENT CONTROL</b> SILT FENCE STATE PROJ. NO. (T.H.) SHEET NO. OF SHEETS
--	--	---




- NOTES:**  
 SEE SPECS. 2533, 2573 & 3886.  
 SILT FENCE TYPE SD USED TO PROTECT CRITICAL AREAS FROM SHEET FLOW, AND AREAS WHERE OTHER SILT FENCES CANNOT BE PLACED, MAXIMUM CONTRIBUTING AREA: 1 ACRE.  
 PLACE SILT FENCE TYPE SD ALONG A CONSTANT ELEVATION.  
 SILT FENCE TYPE SD CAN UTILIZE EITHER A CONCRETE OR WATER FILLED, TEMPORARY MEDIAN BARRIER.  
 ① PLACING STOCK PILES NEXT TO AN ENVIRONMENTALLY SENSITIVE AREA IS NOT RECOMMENDED, WHEN THERE ARE NO FEASIBLE ALTERNATIVES, PLACE SILT FENCE SD AS SHOWN OR AS DIRECTED BY THE ENGINEER.  
 ② CRITICAL AREAS INCLUDE WETLANDS, JUDICIAL DITCHES, STREAMS, WATER BODIES, AND OTHER AREAS REQUIRING PROTECTION.

STANDARD PLAN 5-297.405 DEPARTMENT OF TRANSPORTATION STATE DESIGN ENGINEER	7 OF 8 APPROVED: 2-28-2017 REVISION:	<b>TEMPORARY SEDIMENT CONTROL</b> SUPER DUTY SILT FENCE STATE PROJ. NO. (T.H.) SHEET NO. OF SHEETS
--	--	--



- NOTES:**  
 SEE SPECS. 2573, 3891 & 3893.  
 FOR USE WHEN TEMPORARY PONDING IS NEEDED IN DITCH SECTIONS FOR SEDIMENT CONTROL.  
 MANUFACTURED ALTERNATIVES LISTED ON WOOD'S APPROVED PRODUCTS LIST MAY BE SUBSTITUTED AT NO ADDITIONAL COST.  
 ① ROCK LOG OR SANDBAG TO HOLD STANDPIPE AND ACT AS A SEAL BETWEEN RISER PIPE AND CULVERT.  
 ② PLACE CULVERT APRON AND SLIDE TEMPORARY STANDPIPE INTO CSP OR RIP CULVERT.  
 ③ ALL GEOTEXTILE USED FOR CULVERT PROTECTION SHALL BE MONOFILAMENT IN BOTH DIRECTIONS, MEETING SPEC. 3886 FOR MACHINE SLICES.  
 ④ ROCK LOG OR RIP RAP TO HOLD STANDPIPE AND ACT AS A FILTER BETWEEN RISER PIPE AND CULVERT.  
 ⑤ HEIGHT OVERFLOW NOT TO CAUSE FLOODING OF ROAD OR ADJACENT PROPERTIES.

STANDARD PLAN 5-297.405 DEPARTMENT OF TRANSPORTATION STATE DESIGN ENGINEER	8 OF 8 APPROVED: 2-28-2017 REVISION:	<b>TEMPORARY SEDIMENT CONTROL</b> CULVERT END CONTROLS STATE PROJ. NO. (T.H.) SHEET NO. OF SHEETS
--	--	---



PRELIMINARY WETLAND SUMMARY:  
TOTAL WETLAND IMPACTED AREA: 0.00 SF (0.00 AC)


WETLAND BUFFER AREA PROPOSED

WETLAND BUFFER SIGN: CITY TO FURNISH, DEVELOPER TO INSTALL

7,817 SQFT -REQUIRED 30' WETLAND BUFFER AREA  
7,831 SQFT -PROPOSED AVG. WETLAND BUFFER AREA


WETLAND	Approximate Size (ac)	Wetland Type Classification			MnRAM Classification
		Circular 39	Cowardin	Eggers & Reed	
1	0.10	Type 1	PEM1A	Seasonally Flooded Basin	Manage 2

Buffer MnRAM Class	Base Buffer Width (ft)
Manage 3	20
Manage 2	30
Manage 1	40
Preserve	75





**SANITARY SEWER & WATERMAIN CONSTRUCTION NOTES**

- SANITARY MANHOLE ADJUSTMENT RINGS AND CASTING SHALL BE SEALED WITH INFI-SHIELD UNI-BAND OR APPROVED EQUAL AND THE MANHOLE BARREL JOINTS SHALL BE SEALED WITH INFI-SHIELD GATOR WRAP OR APPROVED EQUAL.
  - SANITARY SERVICE ELEVATIONS ARE AT THE END OF THE SERVICES AS SHOWN, I.E. (INV.=947.6) 15' PAST R/W, NOT INCLUDING RISER PIPE.
  - SERVICE & RISER STATIONING IS FROM DOWNSTREAM MANHOLE.
  - SANITARY SEWER SERVICES, WYES, RISERS, & CLEANOUT SHALL BE 6" PVC SDR 26, UNLESS OTHERWISE NOTED.
  - CURB STOPS ARE LOCATED AT THE EASEMENT LINE..
  - 6" DIP WATERMAIN SHALL BE CL 52. 8" DIP WATERMAIN SHALL BE CL 52..
  - ALL D.I.P. AND D.I.P. FITTINGS TO BE WRAPPED IN POLYETHYLENE.
  - WATER SERVICES SHALL BE 1 1/2" COPPER TYPE "K" NO JOINT/COUPLING IS ALLOWED WITHIN THE CITY ROADWAY.
  - ALL FITTINGS SHALL HAVE MEGA LUGS. (SEE JOINT CHART)
  - ALL SERVICE INVERTS 10' BELOW CURB STOP UNLESS NOTED (\*).
  - CONTRACTOR IS RESPONSIBLE FOR CONFIRMING ALL EXISTING UTILITIES HAVE BEEN REMOVED DURING SITE DEMOLITION.
  - CONTRACTOR IS RESPONSIBLE FOR TRENCH DESIGN & O.S.H.A. REQUIREMENTS.
  - ALL CASTINGS & VALVE BOXES TO BE SET 0.05' BELOW FG ELEVATION.
  - INVERT ELEVATION SHOWN IS LOCATED AT THE END OF SERVICE BELOW THE END OF SERVICE RISER
  - PADS MARKED \*LF=XX.X, SANITARY SERVICE INVERT LESS THAN 4' BELOW PROPOSED BUILDING LOWEST FLOOR.
  - ALL PIPE TO HAVE TRACER WIRE INSTALLED PER CITY OF MINNETONKA REQUIREMENTS.
- NOTE 1: SERVICE INVERT IS UNDER 10' DEEP AT CURB STOP  
NOTE 2: SERVICE INVERT IS OVER 10' DEEP AT CURB STOP



FOREST MEADOW DRIVE LIGHT POLE

NOTE: ALL WATER SERVICES FROM PUBLIC MAIN TO CURB STOP MUST BE ONE CONTIGUOUS PIPE. (NO JOINTS/SPLICES)






**STORM SEWER CONSTRUCTION NOTES**


- PROVIDE R-3250-1 NEENAH CASTINGS OR APPROVED EQUAL ON ALL CATCH BASINS UNLESS OTHERWISE NOTED. SEE MINNETONKA STANDARD PLATE 110 & 120
- PROVIDE 27" DIA. SLAB OPENING FOR R-3250-1 NEENAH CASTINGS ON ALL CATCH BASIN MANHOLES UNLESS OTHERWISE NOTED.
- DRAINTILE SERVICES & CROSSINGS SHALL BE 4" PVC SDR-26 PERFORATED PIPE. PER MINNETONKA STANDARD DETAIL 160 & 170.
- FINAL STRUCTURE OFFSET TO BE VERIFIED BY CONTRACTOR AND INSPECTOR BASED ON MATERIAL SUPPLIED TO PROJECT. FIELD STAKING SHALL BE SET ACCORDING TO BACK-OF-CURB.
- INLET CASTINGS SHALL BE SET 0.17' BELOW GUTTERLINE GRADE. CONCRETE PIPE MUST BE BEDDED TO A MINIMUM OF THE CLASS C BEDDING REQUIREMENTS. SEE MINNETONKA STANDARD SPECS.

NOTE:  
THE LOCATION OF ALL VERTICAL / HORIZONTAL BENDS, SEWER SERVICE INVERTS NEED TO BE VERIFIED BY CITY REPRESENTATIVE BEFORE BACKFILLING PER MN OPS REQUIREMENTS. SEE MINNETONKA SPECS.

STRUCTURE TABLE				
STRUCTURE NAME	TYPE	STRUCTURE SIZE	NEENAH CASTING OR EQUAL	NOTES
100B	OCS	48" DIA.	SPECIAL	
102	CBMH	48" DIA.	R-3250-1	2
103	CB	27" DIA.	R-3250-1	1

- WATER TIGHT SPECIAL NOTE**
  - STRUCTURE SHALL HAVE AN INTEGRAL BASE
  - PIPE CONNECTION TO STRUCTURE WITH PRESS-SEAL
  - WATERSTOP GROUT RING OR APPROVED EQUAL
  - PIPE JOINTS WITHIN 10' OF WATERMAIN WILL BE TONGUE AND GROOVE WITH A HAMILTON KENT SUPERSEAL GASKET OR APPROVED EQUAL MEETING ASTM-443.
  - ALL MH JOINTS WILL BE TONGUE AND GROOVE WITH A HAMILTON KENT SUPERSEAL GASKET OR APPROVED EQUAL MEETING ASTM-443.
- PRETREATMENT STRUCTURE**
  - SAFL BAFFLE WITH SUMP OR APPROVED EQUAL






CURVE TABLE						
CURVE	DELTA	LENGTH	RADIUS	TANGENT	PC	PT
C1	23°45'34"	165.87	400.00	84.15	0+65.83	2+31.71

**CURB LEGEND**


- 08.15 = GUTTER ELEVATION FOR SURMOUNTABLE CURB
- 08.32 = GUTTER ELEVATION FOR B612 CURB
- 08.32T.O. = GUTTER ELEVATION FOR B612 CURB WITH TIP OUT GUTTER
- 07.82 = BITUMINOUS ELEVATION
- ==== = SURMOUNTABLE CURB & GUTTER
- ==== = B612 CURB & GUTTER
- ==== = BITUMINOUS CURB

**NOTE:**  
 MAXIMUM DRIVEWAY WIDTH AT THE PROPERTY LINE IS 20 FEET FOR A TWO-STALL GARAGE AND 30 FEET FOR A THREE-STALL GARAGE.







**NOTE:**  
 ALL CURB AND GUTTER TO BE B612 WITH CURB CUTS AT DRIVEWAYS.



**STREET A**







**TABLE OF QUANTITIES RIPRAP AT RCP OUTLETS**

DIA. OF PIPE (IN.)	L (FT.)	CLASS II (d <sub>50</sub> = 8")			CLASS III (d <sub>50</sub> = 9")			CLASS IV (d <sub>50</sub> = 12")		
		GRANULAR FILTER	TEXTILE FILTER	12" RIPRAP	GRANULAR FILTER	TEXTILE FILTER	18" RIPRAP	GRANULAR FILTER	TEXTILE FILTER	24" RIPRAP
12	8	15.8	8.2	3.8	15.8	8.3	4.4	22.8	8.3	5.9
15	8	19.9	8.2	3.2	19.9	8.3	4.8	29.1	8.4	6.4
18	8	22.4	8.3	4.3	22.4	8.4	6.4	29.8	8.5	8.5
21	8	24.1	8.4	4.7	24.1	8.6	7.1	38.3	8.7	9.4
24	12	29.7	8.5	6.2	33.4	8.8	9.2	37.3	1.9	12.3
27	12	34.4	8.6	6.6	38.2	8.9	9.9	39.2	1.2	13.2
30	14	37.4	8.8	8.2	41.6	1.1	12.3	46.8	1.5	16.4
36	16	45.9	1.1	10.6	50.8	1.6	15.8	58.8	2.1	21.1
42	18	52.8	1.2	12.5	57.8	1.7	18.7	63.8	2.3	24.9
48	28	61.1	1.5	14.8	66.6	2.2	22.2	72.8	2.9	29.6

**TABLE OF QUANTITIES RIPRAP AT RCP-A OUTLETS**

SPAN OF PIPE (IN.)	L (FT.)	CLASS II (d <sub>50</sub> = 8")			CLASS III (d <sub>50</sub> = 9")			CLASS IV (d <sub>50</sub> = 12")		
		GRANULAR FILTER	TEXTILE FILTER	12" RIPRAP	GRANULAR FILTER	TEXTILE FILTER	18" RIPRAP	GRANULAR FILTER	TEXTILE FILTER	24" RIPRAP
22	18	25.4	8.3	4.1	25.6	8.4	6.1	29.8	8.5	8.1
28	12	29.5	8.5	5.7	33.2	8.7	8.5	37.1	8.9	11.3
36	14	37.5	8.8	7.5	41.5	1.1	11.2	45.8	1.5	14.5
43	16	45.9	1.1	9.5	50.5	1.5	14.3	55.3	2.1	19.8
51	18	52.5	1.2	11.3	57.2	1.7	16.9	62.7	2.3	22.5
58	28	59.9	1.3	13.2	65.2	1.9	19.8	78.7	2.5	26.4

**PLAN**

**SECTION A-A**

**SECTION B-B**

**RIPRAP AT RCP OUTLETS**

STATE OF MINNESOTA DEPARTMENT OF TRANSPORTATION



APPROVED: DECEMBER 9, 2013









SCALE: NOT TO SCALE

STD. PLATE NO: 3133D

APPROVED: 1/2008

REVISED: 5/2018





**NOTES:**

- MAY ONLY BE USED AS APPROVED BY CITY ENGINEER.
- SERVICE CONNECTIONS TO BE AT 2 OR 10 O'CLOCK POSITION.

**SERVICE CONNECTION TO CONCRETE SANITARY SEWER**

MACHINE CORED HOLE WITH KOR-N-TEE SERVICE CONNECTION OR APPROVED EQUAL.

POURED IN PLACE CONCRETE SUPPORT FOR SERVICE & CONNECTION (1 C.Y. MIN.)

**SERVICE CONNECTION TO EXISTING PVC SANITARY SEWER**

CUT-IN PVC WYE TO MAN AND ENCASE COMPLETELY IN CONCRETE.

PVC SEWER WYE

PVC SEWER SERVICE

**SERVICE CONNECTION TO NEW PVC SANITARY SEWER**

PVC SEWER WYE

PVC SEWER SERVICE

**PRIVATE CONNECTIONS TO PUBLIC UTILITIES**

SCALE: NOT TO SCALE

STD. PLATE NO: 450

APPROVED: 8/2018

REVISED:

PROPERTY LINE

AS REQUIRED

10' TYPICAL

3'

3"

2"

7'-6" MIN. COVER

7'-6" MIN. COVER

8" CONCRETE BLOCK

8" CONCRETE BLOCK

8" CONCRETE BLOCKS

1 C.Y. CLEAR ROCK COVER W/ 2 LAYERS 4 ML. POLY

HYDRANT: WATEROUS PACER 100 OR APPROVED EQUAL (SEE CITY SPECS)

EXISTING OR FUTURE CURB & GUTTER

VALVE BOX (SEE DETAIL 540)

TEE

IF MAN IS GREATER THAN 7'-8" BURY DEPTH INSTALL HYDRANT WITH VERTICAL BEND & MEGA LUGS

22.25° BEND

GATE VALVE ADAPTOR BY ADAPTOR, INC. OR APPROVED EQUAL.

GATE VALVE

NOTES:

- ALL WATERMAIN, INCLUDING VALVES, FITTINGS AND APPURTENANCES, SHALL BE FULLY ENCASED IN POLYETHYLENE FILM (4 ML).
- ALL GATE VALVES AND BUTTERFLY VALVES SHALL BE FURNISHED WITH AN ADAPTOR TO PREVENT THE BOX FROM SETTLING OR SHIFTING. SEE CITY SPECIFICATIONS.
- ALL MECHANICAL JOINTS SHALL BE RESTRAINED BY MEGALUGS.
- POURED CONCRETE THRUST BLOCK REQUIRED IF STANDARD BLOCKS CANNOT BE PLACED ON UNDISTURBED GROUND.

**HYDRANT**

SCALE: NOT TO SCALE

STD. PLATE NO: 500

APPROVED: 5/2000

REVISED: 8/2018

PROPERTY LINE

AS REQUIRED

18" (MAX)

7'-6" MINIMUM COVER

20°-30°

1-1/2" CURB STOP

6"x6"x2" BRICK

1-1/2" TYPE "K" COPPER PIPE END AT CURB COCK

WATER MAIN

INSTALL METER BOX AND COVER (FORD A-1) OR APPROVED EQUAL OVER ALL CURB STOPS LOCATED IN PAVED DRIVEWAYS AND/OR PARKING AREAS. COVER SHALL BE STAMPED "WATER" FOR CURB STOP BOX.

ROD

CURB BOX

CORPORATION STOP WITH SADDLE

**NOTES:**

- ANY CURB STOP LOCATED IN A PAVED AREA SHALL BE COVERED WITH METER BOX COVER (FORD A-1) OR APPROVED EQUAL.
- ALL SERVICES SHALL BE 1 1/2" MIN. TYPE K COPPER AND SHALL UTILIZE A STAINLESS STEEL SADDLE (SMITH BLAIR 317 OR 372) OR APPROVED EQUAL.
- ALL BRASS FITTINGS SHALL BE "NO LEAD BRASS".
- BASIS OF PAYMENT WILL BE ON THE LINEAR FEET OF SERVICE PIPE INSTALLED AND WATER SERVICE ITEMS INCLUDED IN THE PROPOSAL, WHICH MAY INCLUDE TAP, CORPORATION STOP, CURB STOP, CURB BOX WITH ROD AND TAPPING SADDLE. ALL ITEMS NOT LISTED IN PROPOSAL FORM ARE INCIDENTAL.
- WHEN GROUND WATER IS ENCOUNTERED, A 1 1/2" COPPER "PIGTAIL" WITH CRIMPED END SHALL BE EXTENDED TO 1' ABOVE THE WATER ELEVATION.
- WHEN NEW SERVICE IS INSTALLED IN JOINT TRENCH WITH SANITARY SEWER SERVICE THERE SHALL BE 3' MIN HORIZONTAL & 18" VERTICAL SEPARATION.

**WATER SERVICE CONNECTION**

SCALE: NOT TO SCALE

STD. PLATE NO: 510

APPROVED: 5/2000

REVISED: 8/2018

NOTE: ALL BOLTS, T-BOLTS, NUTS AND RODDING INSTALLED BELOW GRADE SHALL BE ASTM F959 TYPE 304 STAINLESS STEEL. EACH BOLT SHALL BE CLEARLY STAMPED AS A 304 STAINLESS BOLT. (THIS INCLUDES ALL VALVE AND SLEEVE BODY HARDWARE)

TYPE 304 STAINLESS STEEL TAPPING SLEEVE WITH 304 STAINLESS STEEL BOLTS & NUTS

TRACER WIRE SHALL BE INSTALLED UP THE INSIDE OF VALVE BOXES

PVC OR HDPE PIPE

CONCRETE BLOCK

UNDISTURBED EARTH

INSULATED TRACER WIRE AS REQUIRED BY CITY (SEE DETAILS)

CONCRETE THRUST BLOCK

GATE VALVE

PVC OR HDPE PIPE

UNDISTURBED EARTH

COMPACTED GRANULAR BACKFILL OR ROCK

8" CONCRETE BLOCK

**WATERMAIN WET TAP**

SCALE: NOT TO SCALE

STD. PLATE NO: 530

APPROVED: 12/2018

REVISED:

8-7/8"

7-5/8"

8-5/8"

7-1/8"

5-3/4"

5-1/4"

1-1/2"

7-1/8"

7"

8-1/8"

8-1/8"

2-3/8"

7"

8-1/8"

9-7/16"

2-3/4"

7"

8-1/4"

14-3/4"

17-1/4"

NO. 6 ROUND BASE

TYLER DROP LID NO. 6865 OR MUELLER COVER NO. H-10361 OR APPROVED EQUAL LABELED WATER.

GATE VALVE ADAPTOR 1/4" STEEL WITH PROTECTIVE COATING. 1/2" RUBBER GASKET INSTALLED BETWEEN GATE VALVE AND ADAPTOR.

TOP VIEW

SIDE VIEW

FINISHED GRADE

ADJUST TOP TO 1/2" BELOW BLACKTOP GRADE OR 1" BELOW FINISHED BOULEVARD GRADE AND SHALL BE SET SO AS TO PROVIDE 12" OF UPWARD ADJUSTMENT.

GRADE

GATE VALVE BOX, SCREW TYPE, THREE PEGS, 5 1/4" SHAFT, SIZE G BOX 7'-6" EXTENDED NO. 6 ROUND BASE. GATE VALVE AND BOXES SHALL BE: TYLER SERIES NO. 6860 MUELLER NO. H-10357 OR APPROVED EQUAL.

G.V. ADAPTOR AS MANUFACTURED BY ADAPTOR, INC. OR APPROVED EQUAL. SEE ABOVE DETAIL.

7.5" MINIMUM COVER

ALL GATE VALVES SHALL BE OF RESILIENT WEDGE TYPE CONFORMING TO AWWA C515 STANDARDS.

8" CONCRETE BLOCK

**GATE VALVE**

SCALE: NOT TO SCALE

STD. PLATE NO: 540

APPROVED: 1/2008

REVISED: 8/2018

SEE PLAN

45° BEND

OBSTRUCTION

Mech. COMPACTED BACKFILL

WATERMAIN (SEE PLAN)

45° BEND

45° BEND

2" MIN.

2"-4" OF INSULATION IF INSTALLED BELOW STORM SEWER (SEE DETAIL 570)

TIE ALL BENDS

TIE ALL JOINTS WITH MEGALUGS (8 REQ.)

**WATERMAIN OFFSET WITH MEGALUGS**

SCALE: NOT TO SCALE

STD. PLATE NO: 560

APPROVED: 8/2018

REVISED:

GROUND OR STREET SURFACE

GRANULAR MATERIAL

PIPE

INSULATION (SEE NOTE NO. 2)

GRANULAR MATERIAL (SEE NOTE NO. 1)

REQUIREMENTS FOR WIDTH AND THICKNESS OF PLASTIC FOAM INSULATION, PLACED 6" ABOVE TOP OF PIPE FOR VARIOUS PIPE DEPTHS.

"D" DEPTH TO TOP OF PIPE	"W" COMPUTE WIDTH OF INSULATION REQUIRED	"T" THICKNESS OF INSULATION REQUIRED
2 FT. TO 3 FT.	d + 15 FT. - ...	4 IN.
3 FT. TO 4 FT.	d + 13 FT. - ...	4 IN.
4 FT. TO 5 FT.	d + 11 FT. - ...	4 IN.
5 FT. TO 6 FT.	d + 6 FT. - ...	2 IN.
6 FT. TO 7 FT.	d + 4 FT. - ...	2 IN.
7 FT. (ASSUMED FROST LINE)		0 IN.

**NOTES:**

- 6" GRANULAR MATERIAL SHALL BE WELL COMPACTED AND LEVELED TO PERMIT PROPER BEARING FOR INSULATION BOARD.
- INSULATION SHALL BE OF 2 INCH THICK BOARDS OF EXTRUDED OR EXPANDING POLYSTYRENE PLASTIC FOAM SPECIFICALLY DESIGNED FOR USE IN UNDERGROUND CONSTRUCTION AND HAVING A MINIMUM COMPRESSIVE STRENGTH OF 35 P.S.I. SPECIAL NOTE IS TO BE TAKEN THAN THIS TYPE IS DIFFERENT THAN THE TYPE USED IN ORDINARY BUILDING CONSTRUCTION. THE INSULATION BOARD SHALL COMPLY WITH ASTM-D 1621.

**PIPE INSULATION**

SCALE: NOT TO SCALE

STD. PLATE NO: 570

APPROVED: 5/2000

REVISED: 5/2018



5. ANY SPILLS OF HAZARDOUS MATERIALS AND/OR A MINIMUM OF 5-GALLONS PETROLEUM SHALL BE IMMEDIATELY REPORTED TO THE MPCA (STATE DUTY OFFICER: 1.800.422.0798 OR 651.297.8610). ANY SPILLS ABOVE THE REPORTABLE QUANTITIES LIMITS IN THE CODE OF FEDERAL REGULATIONS (CFR) TITLE 40, PART 302 SHALL BE REPORTED TO THE EPA NATIONAL RESPONSE CENTER (1.800.424.8802). IN ORDER TO REDUCE THE RISK OF HAZARDOUS MATERIALS COMING INTO CONTACT WITH STORM WATER, THE FOLLOWING PRACTICES WILL BE FOLLOWED: A) AN EFFORT WILL BE MADE TO STORE ONLY ENOUGH PRODUCTS REQUIRED TO DO THE WORK, B) ALL MATERIALS STORED ON SITE WILL BE STORED IN A NEAT, ORDERLY MANNER IN THEIR APPROPRIATE CONTAINERS AND IF POSSIBLE, UNDER COVER, C) PRODUCTS WILL BE KEPT IN THEIR ORIGINAL CONTAINERS WITH THE ORIGINAL MANUFACTURER'S LABEL UNLESS THE ORIGINAL CONTAINER CANNOT BE RESEALED, IN WHICH CASE THE ORIGINAL LABEL AND MATERIALS SAFETY DATA SHALL BE RETAINED, D) SUBSTANCES WILL NOT BE MIXED WITH ONE ANOTHER UNLESS RECOMMENDED BY THE MANUFACTURER, E) WHENEVER POSSIBLE, ALL OF A PRODUCT WILL BE USED BEFORE DISPOSING OF THE CONTAINER, F) THE MANUFACTURER'S RECOMMENDATIONS FOR PROPER USE AND DISPOSAL WILL BE FOLLOWED, AND G) THE OPERATOR WILL INSPECT DAILY TO ENSURE PROPER USE AND DISPOSAL OF MATERIALS ON SITE. MANUFACTURER'S RECOMMENDED METHODS FOR SPILL CLEANUP WILL BE CLEARLY POSTED AND SITE PERSONNEL WILL BE MADE AWARE OF THE PROCEDURES AND THE LOCATION OF THE INFORMATION AND CLEANUP SUPPLIES.
6. ALL SANITARY WASTE WILL BE COLLECTED BY TEMPORARY SANITARY FACILITIES PROVIDED AT THE SITE BY THE CONTRACTOR THROUGHOUT THE CONSTRUCTION PROJECT. ALL CONSTRUCTION PERSONNEL SHALL UTILIZE TEMPORARY SANITARY FACILITIES, WHICH SHALL BE REGULARLY SERVED BY A COMMERCIAL OPERATOR. TEMPORARY SANITARY FACILITIES SHALL BE PLACED IN A LOCATION WHERE ACCIDENTAL SPILLAGE OF THE FACILITY SHALL NOT DISCHARGE TO THE STORM SEWER SYSTEM.

**TEMPORARY SEDIMENTATION BASINS (14.2)**

1. TEMPORARY SEDIMENTATION BASINS ARE REQUIRED WHERE 10 OR MORE ACRES DRAIN TO A COMMON LOCATION TO PROVIDE TREATMENT OF THE RUNOFF BEFORE IT LEAVES THE CONSTRUCTION SITE OR ENTERS SURFACE WATERS. WHEN A CONSTRUCTION SITE DISCHARGES TO AN IMPAIRED WATER BODY, TEMPORARY SEDIMENTATION BASINS ARE REQUIRED WHERE 5 OR MORE ACRES DRAIN TO A COMMON LOCATION. TEMPORARY SEDIMENTATION BASINS CAN BE CONVERTED TO PERMANENT BASINS AFTER CONSTRUCTION IS COMPLETE.
2. THE TEMPORARY BASIN MUST PROVIDE LIVE STORAGE FOR A CALCULATED VOLUME OF RUNOFF FROM A TWO (2)-YEAR, 24-HOUR STORM FROM EACH ACRE DRAINED TO THE BASIN OR 1,800 CUBIC FEET OF LIVE STORAGE PER ACRE DRAINED, WHICHEVER IS GREATER. WHERE PERMITTEES HAVE NOT CALCULATED THE TWO (2)-YEAR, 24-HOUR STORM RUNOFF AMOUNT, THE TEMPORARY BASIN MUST PROVIDE 3,600 CUBIC FEET OF LIVE STORAGE PER ACRE OF THE BASINS DRAINAGE AREA.
3. PERMITTEES MUST DESIGN THE OUTLET STRUCTURE TO WITHDRAW WATER FROM THE SURFACE TO MINIMIZE THE DISCHARGE OF POLLUTANTS. PERMITTEES MAY TEMPORARILY SUSPEND THE USE OF A SURFACE WITHDRAWAL MECHANISM DURING FROZEN CONDITIONS. THE BASIN MUST INCLUDE A STABILIZED EMERGENCY OVERFLOW TO PREVENT FAILURE OF POND INTEGRITY. PROVIDE ENERGY DISSIPATION FOR THE BASIN OUTLET WITHIN 24 HOURS OF CONNECTION TO A SURFACE WATER.
4. WHERE A TEMPORARY SEDIMENT BASIN MEETING THE REQUIREMENTS OF THE ABOVE IS INFEASIBLE, PERMITTEES MUST INSTALL EFFECTIVE SEDIMENT CONTROLS SUCH AS SMALLER SEDIMENT BASINS AND/OR SEDIMENT TRAPS, SILT FENCES, VEGETATIVE BUFFER STRIPS OR ANY APPROPRIATE COMBINATION OF MEASURES AS DICTATED BY INDIVIDUAL SITE CONDITIONS. IN DETERMINING WHETHER INSTALLING A SEDIMENT BASIN IS INFEASIBLE, PERMITTEES MUST CONSIDER PUBLIC SAFETY AND MAY CONSIDER FACTORS SUCH AS SITE SOILS, SLOPE, AND AVAILABLE AREA ON-SITE. PERMITTEES MUST DOCUMENT THIS DETERMINATION OF INFEASIBILITY IN THE SWPPP.

**FINAL STABILIZATION (4.1)**

1. ALL DISTURBED AREAS SHALL BE PERMANENTLY STABILIZED AS SHOWN ON THE CONSTRUCTION PLANS. METHODS TO ACHIEVE FINAL STABILIZATION INCLUDE: SEED WITH MULCH OR EROSION CONTROL BLANKET AND SOD.
2. ALL AREAS SEEDED BY MEANS OF BROADCAST SEEDING SHALL BE HAND RAKED TO INCORPORATE THE SEEDS INTO THE TOPSOIL.
3. EROSION CONTROL BLANKETS SHALL BE PLACED IN THE DITCH BOTTOM WITHIN 24 HOURS AFTER FINE GRADING. BIOROLLS SHALL BE PLACED IN CONJUNCTION WITH THE BLANKET IN THE DITCH BOTTOMS. THE BIOROLLS ARE INTENDED TO SERVE AS PERMANENT DITCH CHECKS.
4. THE PERMITTEE WILL SUBMIT A NOTICE OF TERMINATION (NOT) WITHIN 30 DAYS AFTER FINAL STABILIZATION. FINAL STABILIZATION SHALL CONSIST OF A UNIFORM PERENNIAL VEGETATIVE COVER OF AT LEAST 70 PERCENT OF THE EXPECTED FINAL VEGETATIVE GROWTH DENSITY OR OTHER PERMANENT COVER HAS BEEN ESTABLISHED OVER THE ENTIRE PERVIOUS SURFACES.
5. PERMIT COVERAGE TERMINATES ON INDIVIDUAL LOTS IF THE STRUCTURES ARE FINISHED AND TEMPORARY EROSION PREVENTION AND DOWNGRADIANT PERIMETER CONTROL IS COMPLETE, THE RESIDENCE SELLS TO THE HOMEOWNER, AND THE PERMITTEE DISTRIBUTES THE MPCA'S "HOMEOWNER FACT SHEET" TO THE HOMEOWNER.

**PERMIT TERMINATION CONDITIONS (13.1)**

1. PERMITTEES MUST COMPLETE ALL CONSTRUCTION ACTIVITY AND MUST INSTALL PERMANENT COVER OVER ALL AREAS PRIOR TO SUBMITTING THE NOTICE OF TERMINATION (NOT). VEGETATIVE COVER MUST CONSIST OF A UNIFORM PERENNIAL VEGETATION WITH A DENSITY OF 70 PERCENT OF ITS EXPECTED FINAL GROWTH. VEGETATION IS NOT REQUIRED WHERE THE FUNCTION OF A SPECIFIC AREA DICTATES NO VEGETATION, SUCH AS IMPERVIOUS SURFACES OR THE BASE OF A SAND FILTER.
2. FOR RESIDENTIAL CONSTRUCTION ONLY, PERMIT COVERAGE TERMINATES ON INDIVIDUAL LOTS IF THE LOT IS SOLD TO THE HOMEOWNER, STRUCTURES ARE FINISHED, AND PERMANENT COVER HAS BEEN ESTABLISHED. FOR LOTS THAT ARE SOLD TO THE HOMEOWNER WHERE PERMANENT COVER HAS NOT BEEN ESTABLISHED, COVERAGE TERMINATES IF TEMPORARY EROSION PREVENTION AND DOWNGRADIANT PERIMETER CONTROL IS PROPERLY INSTALLED, AND THE PERMITTEE DISTRIBUTES THE MPCA'S "HOMEOWNER FACT SHEET" TO THE HOMEOWNER.
3. WHEN SUBMITTING THE NOT PERMITTEES MUST INCLUDE EITHER GROUND OR AERIAL PHOTOGRAPHS SHOWING THE REQUIREMENTS OF 13.2 HAVE BEEN MET. PERMITTEES ARE NOT REQUIRED TO TAKE PHOTOGRAPHS OF EVERY DISTINCT PART OF THE SITE, HOWEVER THE CONDITIONS PORTRAYED MUST BE SUBSTANTIALLY SIMILAR TO THOSE AREAS THAT ARE NOT PHOTOGRAPHED. PHOTOGRAPHS MUST BE CLEAR AND IN FOCUS AND MUST INCLUDE THE DATE THE PHOTO WAS TAKEN.

**RECORDS RETENTION (5.1&6.1)**

1. RECORDS MUST BE KEPT ON SITE IN A PHYSICAL OR ELECTRONIC FORMAT DURING NORMAL WORKING HOURS WITH PERSONNEL WHO HAVE OPERATIONAL CONTROL OVER THE APPLICABLE PORTION OF THE SITE. THESE RECORDS MUST INCLUDE:
  - A. COPY OF THE SWPPP AND AMENDMENTS
  - B. TRAINING DOCUMENTATION
  - C. INSPECTION AND MAINTENANCE RECORDS
2. THIS SWPPP WILL BE AMENDED AS NEEDED AND/OR AS REQUIRED BY PROVISIONS OF THE PERMIT. ANY CHANGES TO THE SWPPP SHALL BE NOTED BELOW AND ON THE APPLICABLE PLAN SHEETS. ANY AMENDMENTS TO THE SWPPP MUST BE INCORPORATED WITHIN 7 DAYS TO INCLUDE ADDITIONAL OR MODIFIED BMPS.
3. THE CONTRACTOR WILL RECORD CHANGES TO THE SWPPP AND MAINTAIN DOCUMENTATION OF THESE CHANGES ON SITE AT ALL TIMES. A SUMMARY MAINTENANCE/CONSTRUCTION OBSERVATION REPORT WILL BE RECORDED AFTER EACH SITE INSPECTION/OBSERVATION.
4. THE CONTRACTOR WILL BE RESPONSIBLE TO MAINTAIN AND REPAIR THE EROSION AND SEDIMENT CONTROL BMP'S UNTIL FINAL STABILIZATION IS COMPLETE AND A NOTICE OF TERMINATION (NOT) IS SUBMITTED.

ITEM DESCRIPTION	UNIT	ESTIMATED QUANTITY
CONSTRUCTION LIMIT STAKING	LF	2871
ROCK CONSTRUCTION ENTRANCE	EA	1
ROCK CONSTRUCTION ENTRANCE MAINTENANCE	EA	1
EROSION CONTROL FENCE	LF	4188
MAINTENANCE OF PERIMETER EROSION CONTROL	YR	1
BIOROLL DITCH CHECK	EA	0
STREET SWEEPING AND VACUUMING	YR	1
STORM DRAIN INLET PROTECTION	EA	6
TEMPORARY SEED AND MULCH	AC	2.6
PERMANENT SEED AND MULCH	AC	2.4
MAINTAIN SEED AND MULCH	AC	2.4
EROSION CONTROL BLANKET (MNDOT CAT. 20)	SY	210
VEHICLE AND EQUIPMENT CLEANING	LS	1
VEHICLE AND EQUIPMENT FUELING	LS	1
VEHICLE AND EQUIPMENT MAINTENANCE	LS	1
SPILL PREVENTION AND CONTROL	LS	1
ROCK BERM EROSION CONTROL	LS	1
RIP RAP ENERGY DISSIPATOR	CY	22.4
INDIVIDUAL LOT HOME CONSTRUCTION EROSION CONTROL	EA	5

AMENDMENT	BY	DATE



2422 Enterprise Drive  
Mendota Heights, MN 55120  
(651) 681-1914  
Fax: 681-9488  
www.pioneereng.com

I hereby certify that this plan was prepared by me or under my direct supervision and that I am a duly Licensed Professional Engineer under the laws of the State of Minnesota

Name: John M. Molinaro  
Reg. No.: 45831  
Date: 10-27-2023

Revisions:  
1. 12-07-2023 City/County/Watershed Comments  
2. 12-14-2023 City Comments  
3. 1-2-2024 City Comments  
4. 3-5-2024 City Comments


Date: 10-27-23  
Designed: JMM  
Drawn: MSN/PDS

**STORM WATER POLLUTION  
PREVENTION PLAN**

**NORTON HOMES**  
18215 45TH AVENUE NORTH  
PLYMOUTH, MINNESOTA 55446


**WOODHAVEN**  
MINNETONKA, MINNESOTA

# MPCA's Construction Stormwater Special Waters Search




10/16/2023, 10:09:13 AM

- Waterbody Units - Lakes (1)
- Waterbody Units - Streams (1)
- Impaired Lakes without additional construction requirements
- Impaired Lakes with additional construction requirements
- Impaired Streams without additional construction requirements
- Impaired Streams with additional construction requirements




Metropolitan Council, MetroGIS, Three Rivers Park District, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA, Esri, NASA, NGA, USGS, FEMA

Esri, NASA, NGA, USGS, FEMA | Esri Community Maps Contributors, Metropolitan Council, MetroGIS, Three Rivers Park District, Esri, HERE, Garmin, SafeGraph, GeoTechnologies, Inc, METI/NASA, USGS, EPA, NPS, US Census Bureau, USDA | MPCA; US Census Bureau; MNDOT; | Minnesota Pollution Control Agency



**LEGEND**


1	SUBCATCHMENT
200P	POND
EP-025a	LINK






**LEGEND**

1	SUBCATCHMENT
200P	POND
EP-025a	LINK







**PLANTING SCHEDULE**

KEY	COMMON NAME/SCIENTIFIC NAME	ROOT	QUANTITY
<b>OVERSTORY TREES</b>			
	SENTRY LINDEN/TILIA AMERICANA 'SENTRY'	3" B&B	5
	NORTHERN PIN OAK/QUERCUS ELLIPSOIDALIS	3" B&B	7
	THORNLESS HONEYLOCUST/GLEDITSIA TRIACANTHOS VAR INERMIS	3" B&B	3
	RIVER BIRCH/BETULA NIGRA 'HERITAGE' (CLUMP)	14' B&B	9
	NORTHWOOD MAPLE/ACER RUBRUM 'NORTHWOOD'	3" B&B	5
	SWAMP WHITE OAK/QUERCUS BICOLOR	3" B&B	8
	AUTUMN BLAZE MAPLE/Acer x freemanii 'Jeffersred'	3" B&B	5
<b>EVERGREEN TREES</b>			
	WHITE PINE/PINUS STROBUS	8' B&B	7
	BLACK HILLS SPRUCE/PICEA GLUACA VAR DENSATA	8' B&B	11

PROPOSED TREES:  
 OVERSTORY: 42 TREES @3" = 126"  
 CONIFER: 18 TREES @8" = 144"  
 PROPOSED RAIN GARDEN SEED AREAS (0.25" FOR EACH 1 SF OF SEED): 9,420 SF = 2,355"

**Mitigation:**  
 High Priority: 391" overstory (19 trees removed)  
 High Priority: 145' conifer (6 trees removed)  
 Significant: 10" (5 trees removed)

SEE TREE PRESERVATION PLAN FOR TREE INVENTORY AND PRESERVATION DETAILS


**LANDSCAPE NOTES**

- THE LANDSCAPE CONTRACTOR SHALL VISIT THE PROJECT SITE TO BECOME FAMILIAR WITH THE EXISTING CONDITIONS PRIOR TO SUBMITTING A BID.
- THE LANDSCAPE CONTRACTOR SHALL NOTIFY THE LANDSCAPE ARCHITECT OF PROPOSED PHYSICAL START DATE AT LEAST 7 DAYS IN ADVANCE.
- THE LANDSCAPE CONTRACTOR SHALL BE RESPONSIBLE FOR THE FIELD VERIFICATION OF ALL EXISTING UTILITY LOCATIONS ON THE PROJECT SITE WITH COPPER STATE ONE CALL 1-800-252-1166 PRIOR TO COMMENCING WORK. THE LANDSCAPE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION AND REPAIR OF EXISTING UTILITIES DAMAGED DURING CONSTRUCTION AT NO COST TO THE OWNER. NOTIFY THE LANDSCAPE ARCHITECT OF ANY CONFLICTS TO FACILITATE PLANT RELOCATION.
- GRADING TO BE PERFORMED BY OTHERS.
- NO PLANT MATERIAL SHALL BE INSTALLED UNTIL GRADING AND CONSTRUCTION HAS BEEN COMPLETED IN THE IMMEDIATE AREA.
- ALL PLANT MATERIAL SHALL MEET THE STANDARDS FOUND IN THE AMERICAN ASSOCIATION OF NURSERYMEN-AMERICAN STANDARD FOR NURSERY STOCK.
- ALL CONTAINER MATERIAL TO BE GROWN IN THE CONTAINER A MINIMUM OF SIX (6) MONTHS PRIOR TO PLANTING ON SITE.
- DECIDUOUS AND CONIFEROUS TREES SHALL NOT BE STAKED, BUT THE LANDSCAPE CONTRACTOR MUST GUARANTEE STABILITY TO A WIND SPEED OF 60 M.P.H.
- THE LANDSCAPE CONTRACTOR SHALL PROVIDE A MINIMUM GUARANTEE OF ONE YEAR ONE TIME REPLACEMENT ON NEW PLANT MATERIALS. GUARANTEE SHALL BE AGREED UPON BY DEVELOPER/BUILDER AND LANDSCAPE CONTRACTOR.
- THE LANDSCAPE ARCHITECT RESERVES THE RIGHT TO REJECT ANY PLANTS WHICH ARE DEEMED UNSATISFACTORY BEFORE, DURING OR AFTER INSTALLATION.
- IF THERE IS A DISCREPANCY BETWEEN THE NUMBER OF PLANTS SHOWN ON THE PLAN AND THE NUMBER SHOWN ON THE PLANT LIST, THE NUMBER SHOWN ON THE PLAN WILL TAKE PRECEDENCE.
- THE LANDSCAPE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL MULCHES AND PLANTING SOIL QUANTITIES TO COMPLETE WORK SHOWN ON THE PLAN. THE LANDSCAPE CONTRACTOR SHALL VERIFY ALL QUANTITIES SHOWN ON THE PLANT SCHEDULE.
- COMMERCIAL GRADE POLY LAWN EDGING SHALL BE INSTALLED WHERE NOTED.
- THE LANDSCAPE CONTRACTOR SHALL REPAIR ALL DAMAGE TO THE SITE CAUSED BY THE PLANTING OPERATION AT NO COST TO THE OWNER.
- THE LANDSCAPE CONTRACTOR SHALL KEEP PAVEMENTS CLEAN UNSTAINED. ALL PEDESTRIAN AND VEHICLE ACCESS TO BE MAINTAINED THROUGHOUT CONSTRUCTION PERIOD. ALL WASTES SHALL BE PROMPTLY REMOVED FROM THE SITE. ANY DAMAGE TO EXISTING FACILITIES SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR COMPLYING WITH ALL APPLICABLE CODES, REGULATIONS AND PERMITS GOVERNING THE WORK.
- STORAGE OF MATERIALS OR SUPPLIES ON-SITE WILL NOT BE ALLOWED.


**NATIVE RAIN GARDEN SEED MIX**  
 MNDOT 34-262 OR NATIVE EQUIVALENT


Common Name	Scientific Name	Rate (lb/ft <sup>2</sup> )	Rate (lb/1000)	% of Mix (% by wt)	Seeds/ sq ft
<b>34-262 Wet Prairie</b>					
big bluestem	<i>Andropogon gerardi</i>	1.12	1.03	8.26%	3.87
fringed brome	<i>Bromus ciliatus</i>	1.68	1.50	10.35%	6.08
bluejoint	<i>Calamagrostis canadensis</i>	0.04	0.04	0.27%	4.00
virginia wild rye	<i>Elymus virginicus</i>	1.98	1.75	12.07%	2.70
fall fescue grass	<i>Lycopodium gracile</i>	0.17	0.15	1.02%	3.90
low meadow grass	<i>Clitoria striata</i>	0.12	0.11	0.79%	3.50
swtgrass	<i>Panicum virgatum</i>	0.64	0.75	5.18%	3.85
low bluegrass	<i>Poa palustris</i>	0.22	0.20	1.39%	8.80
meadow grass	<i>Scirpobolus nutans</i>	0.58	0.50	3.44%	2.30
grease cordgrass	<i>Scirpus pedicellatus</i>	0.58	0.50	3.41%	1.20
	<b>Total Grasses</b>	<b>7.29</b>	<b>6.50</b>	<b>44.72%</b>	<b>40.80</b>
wooly sedge	<i>Carex pedis</i>	0.08	0.05	0.32%	0.47
tufted sedge	<i>Carex stricta</i>	0.02	0.02	0.17%	0.48
fox sedge	<i>Carex vesicaria</i>	0.11	0.10	0.69%	3.50
dark green bulrush	<i>Scirpus atrovirens</i>	0.11	0.10	0.72%	17.74
woolgrass	<i>Scirpus cypripus</i>	0.03	0.03	0.19%	18.00
	<b>Total Sedges and Rushes</b>	<b>0.34</b>	<b>0.30</b>	<b>2.09%</b>	<b>38.19</b>
Canada anemone	<i>Anemone canadensis</i>	0.03	0.03	0.21%	0.09
marsh milkweed	<i>Asclepias incarnata</i>	0.00	0.00	0.00%	0.14
Canada tick trefoil	<i>Desmodium canadense</i>	0.58	0.50	3.41%	1.00
flat-topped aster	<i>Doellingeria umbellata</i>	0.08	0.05	0.34%	1.20
common horseweed	<i>Eupatorium perfoliatum</i>	0.03	0.03	0.20%	2.00
grass-leaved goldenrod	<i>Euthamia graminifolia</i>	0.02	0.02	0.11%	2.00
spotted Joe-pye-weed	<i>Eutrochium maculatum</i>	0.04	0.04	0.30%	1.50
autumn snakeroot	<i>Helenium autumnale</i>	0.08	0.05	0.32%	2.30
swamp sunflower	<i>Helianthus grosseserratus</i>	0.00	0.00	0.00%	0.30
great blazing star	<i>Liatris pycnostachya</i>	0.02	0.02	0.17%	0.10
great lobelia	<i>Lobelia siphilitica</i>	0.01	0.01	0.00%	1.40
blue monkey flower	<i>Mimulus rigens</i>	0.01	0.01	0.05%	6.40
virginia mountain mint	<i>Pycnanthemum virginicum</i>	0.00	0.00	0.00%	6.50
red-stemmed aster	<i>Symphoricarpos punctatum</i>	0.09	0.08	0.59%	2.40
blue vervain	<i>Verbena hastata</i>	0.17	0.15	1.06%	5.25
hunched ironweed	<i>Vernonia fasciculata</i>	0.03	0.03	0.23%	0.30
Cuba's root	<i>Veronica virginicum</i>	0.02	0.02	0.14%	8.00
golden alexanders	<i>Zizia aurea</i>	1.28	0.25	1.79%	1.00
	<b>Total Forbs</b>	<b>1.88</b>	<b>1.50</b>	<b>10.40%</b>	<b>40.03</b>
<b>Oats or winter wheat (see note at beginning of list for recommended dates)</b>					
	<b>Total Cover Crop</b>	<b>6.95</b>	<b>6.20</b>	<b>42.74%</b>	<b>2.78</b>
	<b>Totals</b>	<b>18.20</b>	<b>14.80</b>	<b>100.00%</b>	<b>121.05</b>
<b>Purpose:</b>	Wet prairie reconstruction for wetland mitigation or ecological restoration.				
<b>Planting Area:</b>	Tallgrass Aspen Parklands, Prairie Parkland, and Eastern Broadleaf Forest Provinces. MvDOT Districts 2(west), 5B, 4, Metro, 6, 7 & 8.				

**DECIDUOUS TREE PLANTING DETAIL**



**CONIFEROUS TREE PLANTING DETAIL**





**TREE NOTES:**

- 641 HIGH PRIORITY TREE
- 777 SIGNIFICANT TREE
- 771 TREE TAGGED AND INVENTORIED BUT NOT PROTECTED BY ORDINANCE DUE TO SIZE, SPECIES, OR CONDITION (AS PER CITY)
- 641 HIGH PRIORITY TREE TO BE REMOVED
- 777 SIGNIFICANT TREE TO BE REMOVED
- 771 UNPROTECTED TREE TO BE REMOVED
- NON-EXEMPT REMOVAL
- TREE/SILT FENCE (TYP)
- TREE REMOVAL EXEMPT FROM MITGATION

**Review Notes (as per City of Minnetonka)**

<b>h</b>	high priority tree	TOTAL = 274 trees
	Allowable removals = 35% or <b>95 trees</b>	
<b>s</b>	significant trees	TOTAL = 117 trees
	Allowable removals = 50% or <b>58 trees</b>	
<b>n</b>	Not protected by ord. due to size, species, or condition	TOTAL = 105 trees


Significant Trees Saved: 100  
 Significant Trees Removed: 17 (14.5%)  
 High Priority Trees Saved: 184  
 High Priority Trees Removed: 90 (32.8%)  
 Total Trees Removed: 107

Remove Exempt: 77 trees  
 Remove non-exempt (must be mitigated): 30

Mitigation:  
 High Priority: 391" overstory (19 trees removed)  
 High Priority: 145' conifer (6 trees removed)  
 Significant: 10" (5 trees removed)

- OFF SITE TREE
- TREE TO BE SAVED
- TREE TO BE REMOVED

**TREE PROTECTION DETAIL**



NOTE: TREES TO BE SAVED SHALL BE FENCED OFF WITH BRIGHT ORANGE POLYETHYLENE SAFETY NETTING AND STEEL STAKES AT THE DRIP LINE, OR AS DIRECTED BY THE OWNER'S REP. TO INSURE AGAINST DAMAGE BY VEHICLES, COMPACTION OF SOILS AND/OR THE CHEMICAL ALTERATION OF SOILS DUE TO CONCRETE WASHOUT, PAINTS AND LEAKAGE OR SPILLAGE OF ANY TOXIC MATERIALS.

**TREE PRESERVATION NOTES**

BEFORE LAND CLEARING BEGINS, CONTRACTOR SHOULD MEET WITH THE CONSULTANT ON SITE TO REVIEW ALL WORK PROCEDURES, ACCESS ROUTES, STORAGE AREAS, AND TREE PROTECTION MEASURES.


NO FILL SHOULD BE PLACED AGAINST THE TRUNK, ON THE ROOT CROWN, OR WITHIN THE DRIP LINE AREA OF ANY TREES THAT ARE TO BE SAVED.

NO GRADING, TRENCHING OR PLACEMENT OF EQUIPMENT IS ALLOWED IN THE TREE PROTECTION AREA.

WORK PERFORMED WITHIN THE TREE PROTECTION AREA SHOULD BE DONE BY HAND AND UNDER THE SUPERVISION OF THE CONSULTING ARBORIST.

PRUNING OF OAK TREES MUST NOT TAKE PLACE FROM APRIL 15 TO JULY 15 TO PREVENT THE SPREAD OF OAK WILT DISEASE.


IF WOUNDING OF OAK TREES OCCUR ANYTIME BETWEEN APRIL TO AUGUST, A NON-TOXIC WOUND DRESSING MUST BE APPLIED IMMEDIATELY. (EXCAVATORS MUST HAVE A NON-TOXIC TREE WOUND DRESSING WITH THEM ON DEVELOPMENT SITES).



SEE SHEETS T2-3 FOR TREE INVENTORY  
 TREE INVENTORY PROVIDED BY MIDWEST NATURAL RESOURCES, INC.  
 KEN ARNDT








**PROPOSED CONSERVATION EASEMENT DESCRIPTION:**

An easement for conservation purposes lying over, under and across all that part of Lots 4 and 5, Block 1, WOODHAVEN, according to the recorded plat thereof, Hennepin County, Minnesota. Said easement lies within the following line to be described:

Commencing at the northeast corner of said Lot 5, thence North 89 degrees 21 minutes 40 seconds West assumed bearing along the north line of said Lot 5, 142.83 feet to the point of beginning; thence South 29 degrees 39 minutes 01 seconds West, 75.28 feet; thence South 49 degrees 35 minutes 29 seconds West, 60.50 feet; thence North 64 degrees 33 minutes 16 seconds West, 21.67 feet, thence North 14 degrees 36 minutes 47 seconds West, 19.60 feet; thence North 64 degrees 33 minutes 16 degrees West, 22.53 feet; thence North 88 degrees 34 minutes 16 seconds West, 11.07 feet; thence North 21 degrees 32 minutes 43 seconds West, 82.12 feet to the north line of said Lot 4, thence South 89 degrees 21 minutes 40 seconds East along the north lines of said Lots 4 and 5, 176.02 feet to the point of beginning.



\* This sketch does not purport to show the existence or nonexistence of any encroachments from or onto the hereon described land, easements of record or unrecorded easements which affect said land or any improvements to said land.

Description Sketch for:  
NORTON HOMES INC

Cad File: 123127- CONSERV  
EASEMENT.dwg  
Date: 3-18-24  
Folder #: 8892  
Drawn by: KSO

**PIONEERengineering**  
CIVIL ENGINEERS LAND PLANNERS LAND SURVEYORS LANDSCAPE ARCHITECTS  
(651) 681-1914  
Fax: 681-9488  
www.pioneereng.com  
2422 Enterprise Drive  
Mendota Heights, MN 55120