

Completed Building Permit Application

Swimming Pools, Hot Tubs & Spas

Checklist of Required Items

This checklist is designed to help you provide the information required for a timely plan review. Listed below are the document's and plan information needed by the plan examiner. Please check the appropriate box as you prepare your plans and application.

One copy of Certificate of Survey or Site Plan showing: Elevations (Grade)	One cany of Cartificate of Survey or Site Dlan chaying
Location of swimming pool, hot tub or spa Location of pool aprons Location of pool equipment Location of fencing Location of setbacks Fencing specifications Pool specifications and engineering Pump, filter and heater specifications showing U.L., AGA, NSF approval COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	One copy of Certificate of Survey of Site Plan snowing:
Location of pool aprons Location of pool equipment Location of fencing Location of setbacks Fencing specifications Pool specifications and engineering Pump, filter and heater specifications showing U.L., AGA, NSF approval COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Elevations (Grade)
Location of pool equipment Location of fencing Location of setbacks Fencing specifications Pool specifications and engineering Pump, filter and heater specifications showing U.L., AGA, NSF approval COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Location of swimming pool, hot tub or spa
Location of fencing Location of setbacks Fencing specifications Pool specifications and engineering Pump, filter and heater specifications showing U.L., AGA, NSF approval COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Location of pool aprons
Location of setbacks Fencing specifications Pool specifications and engineering Pump, filter and heater specifications showing U.L., AGA, NSF approval COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Location of pool equipment
Fencing specifications Pool specifications and engineering Pump, filter and heater specifications showing U.L., AGA, NSF approval COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Location of fencing
Pool specifications and engineering Pump, filter and heater specifications showing U.L., AGA, NSF approval COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Location of setbacks
Pump, filter and heater specifications showing U.L., AGA, NSF approval COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Fencing specifications
COMPLIANCE AGREEMENT Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Pool specifications and engineering
Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	Pump, filter and heater specifications showing U.L., AGA, NSF approval
Minnetonka Code of Ordinances - Section 805 Swimming pools, hot tubs & spas must be completely enclosed by a fence or wall. The wall or fence (and gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date:	
gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming pool must be at least 15 feet from an exiting portion of sewage system. I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water. Signature of owner/contractor: Date: Date:	
Signature of owner/contractor: Date:	gates) must be at least 5 feet in height. A fence must be constructed of at least a number 11 gauge woven wire mesh corrosion resistant material or other materials approved by the Building Official. Openings in vertical fencing may not exceed 4 inches. Fence posts must be decay or corrosion resistant and must be set in concrete bases or other suitable material. The opening between the bottom of the fence and the ground or other surface may not be more than 3 inches. Lockable covers are not allowed as a substitute for a fence or wall. Openings or points of entry into the area enclosure must be equipped with gates. Gates must be equipped with self-closing and self-latching devices capable of being locked, placed on top of the gate or another place inaccessible to small children. A swimming pool and its appurtenances must be located at least 10 feet from an existing portion of sewage system. The water supply line for a swimming
owner/contractor: Date:	I agree that these requirements will be complied with prior to filling the swimming pool, hot tub or spa with water.
Property Address	
Troporty Address:	owner/contractor: Date: